

QBIC version comparison chart

Date: February 2007

(modified items indicated in italics)

Criteria	Version 1.5	Version 2.0
CPU	PXA263, 400MHz	PXA263, 400MHz
Internal flash	32MB	32MB
Memory	Flash 32MB, SDRAM PC100, 256MB	Flash 32MB, SDRAM PC100, 256MB
USB	Philips ISP1161, 2 ports, USB spec v2.0 host controller, full-speed (12MBit/s) support	Philips ISP1161, 2 ports, USB spec v2.0 host controller, full-speed (12MBit/s) support
<i>Bluetooth</i>	<i>Infineon ROK104001, Bluetooth 1.1</i>	<i>Infineon PBA31307 Singlestone, Bluetooth 1.2, Master-slave support</i>
Removable media	MMC socket, supports capacities <=1GByte, selected media types only	MMC socket, supports capacities <=1GByte, selected media types only
Display	VGA 640x480	VGA 640x480
<i>Belt</i>	<i>Leather, black, integrated flex print, 2 USB host ports, 2 Serial (RS232), 1 VGA port, 1 power supply connector, internal battery</i>	<i>Improved stability of Version 1.5, identical interfaces</i>
OS	<i>Linux 2.6.10, Debian Sarge distribution</i>	<i>Linux 2.6.17, Familiar embedded Linux distribution with package management</i>
Power	Internal battery Li-Ion 700mAh, rechargeable; Ext. battery Li-Ion 4.3Ah, rechargeable; Mains power: 5V	Internal battery Li-Ion 700mAh, rechargeable; Ext. battery Li-Ion 4.3Ah, rechargeable; Mains power: 5V
<i>Buckle case</i>	<i>Cover: moulded plastic, white/beige; backside: metal, silver</i>	<i>Cover: drilled plastic, black; backside: metal, gold</i>